



Specifications Page

Product	Cool-line I	Cool-line II
Fans	1/300 mm crossflow	2/300 mm crossflow
Airflow (free air)	20/30 CFM	30/50 CFM
Noise level	16 dBA	19 dBA
Control	Proportional	Proportional
Power consumption	5 watts	9 watts
Dimensions, face (aluminum)	15.375"l x 3.5"w x 3.75"d 391x89x96mm	30.25"l x 3.375"w x 3.75"d 768x86x96mm
Dimensions, face(wood)	16.375"l x 3.5"w x 2.5"d 416x89x64mm	30"l x 3.5"w x 2.5"d 762x89x64mm
Dimensions, r. o. (aluminum)	14.25"l x 2.5"w 362x64mm	29.125"l x 2.5"w 740x64mm
Dimensions, r. o. (wood)	14.75"l x 2.125"w 375x54mm	28.25"l x 2.125"w 718x54mm
Weight, boxed (lbs/kgm)	2/9 (aluminum); 2.5/1.2 (wood)	2.5/1.2 (aluminum); 3/1.4(wood)
ATM part number - wood	00-521-XX-I (intake-substitute wood codes below for "XX") 00-521-XX-E (exhaust)	00-522-XX-I (intake-substitute wood codes below for "XX") 00-522-XX-E (exhaust)
ATM part number - metal	00-531-01	00-532-01

Wood species: Red Oak (RO), White Oak (WO) Maple (MA), Cherry (CH), Q-sawn White Oak (QO), White Pine (WP), So. Yellow Pine (YP), Black Walnut (BW), Ash (AS), Poplar (PO), White Birch (WB), Red Birch (RB), Phil. Mahogany (PM), Sassafras (SA), Cypress (CY), Beech (BE), Cedar (CE), Bamboo (BA), Purple Heart (PH), Jajoba (JA), Ant. Heart Pine (AP), Hond. Mahogany (HM), Hickory (HI), VG

Fir (VG), Redwood (RW), Teak (TE), and Alder (AL).