



## Specifications Page

Product	Cool-stack I	Cool-stack II	Cool-stack III
<b>Fans</b>	4/80mm	6/120mm	4/120mm
<b>Airflow, front exh. (free air)</b>	40 CFM	52/133 CFM (lo/hi)	22/60 (idle/hi)
<b>Airflow, rear exh. (free air)</b>	N/A	30/95 CFM	24 CFM (full speed)
<b>Airflow, top exh. (free air)</b>	N/A	14/30 CFM	N/A
<b>Noise level</b>	19 dBA	21-42 dBA	18/24 dBA
<b>Control</b>	90°F thermal control	2 speeds, thermally controlled	Idle + 90°F thermally controlled
<b>Power consumption</b>	7 watts	17-28 watts	7/9 watts (idle/hi)
<b>Dimensions</b>	1.75”h x 19”w x 8”d	3.5”h x 19”w x 18”d	1.75”h x 19”w x 18”d
<b>Dimensions, metric</b>	45h x 483w x 200d mm	90h x 483w x 457d mm	45h x 483w x 406d mm
<b>Weight, boxed (lbs/kgm)</b>	8/3.7	16/7.3	11/5
<b>ATM part number</b>	00-301-03 (exhaust) 00-302-02 (intake)	00-303-01	00-304-01